

Description

50 Ohm Coaxial cable

low loss for wireless communication systems

Coaxial Cables

CAVEL®

since 1968

Data Sheet

WL300ZHN



Ø	1,80	4,80	4,97	5,57	7,60
	(Cu)	(PEG/PE)	(Al/Pet/Al/Sur)	(CuSn)	(LSZH)

Construction data

Inner conductor of plain copper	(Cu)	Ø 1,80 ± 0,02	mm
Dielectric of physical foam polyethylene + outer PE skin	(PEG/PE)	Ø 4,80 ± 0,10	mm
Aluminium/Polyester/Aluminium/Surlyne tape longitudinally overlapped and bonded to the dielectric	(Al/Pet/Al/Sur)		
Braid of tinned copper wires	(CuSn)		
Braid optical coverage (IEC 96-1)		84	%
Diameter over Braid		Ø 5,57	mm
Outer sheath of Thermoplastic material - black - halogen-free, low smoke, flame retardant and UV-resistant	(LSZH)	Ø 7,60 ± 0,10	mm

Printed each meter by yellow ink-jet :

CAVEL WL 300 ZHN 50 Ohm LOW LOSS WI-FI/RF - MADE IN ITALY - ss/aa - m
(ss=settimana aa=anno)

(ss=week, aa=year) (m=meter marking)

Physical data

Weight of copper conductors	43,90	kg/km
Total weight of cable	83,80	kg/km
Minimum bending radius	75	mm
Maximum cable pulling strength	540	N
Minimum installation temperature	-5	°C
Operating temperature	-25 / +80	°C

Electrical data

Characteristic impedance	50 ± 2	Ohm
Capacitance	78	pF/m
Velocity Ratio	86 %	
Inner conductor resistance	7	Ohm/km
Outer conductor resistance	7,30	Ohm/km
Loop resistance	14,30	Ohm/km
Sheat Insulation voltage (spark test)	5	kV
Maximum current (Ieff)	18	A
Structural return loss (SRL)	Max. power	
5 - 470 MHz	>30 dB	30 MHz 2.090 W 50 MHz 1.620 W
470 - 1000 MHz	>28 dB	150 MHz 920 W 220 MHz 760 W
1000 - 2000 MHz	>26 dB	450 MHz 520 W 900 MHz 360 W
2000 - 3000 MHz	>22 dB	1500 MHz 280 W 1800 MHz 250 W
		2000 MHz 240 W 2500 MHz 210 W
		5800 MHz 130 W

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

05/06/2017

Responsible

Alberto Scardovi

Description

50 Ohm Coaxial cable

low loss for wireless communication systems

**Data Sheet****WL300ZHN**

Screening Attenuation (SA)

>90 dB

Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
50	4,10	1500	24,50
150	7,00	1800	27,00
220	8,60	2000	28,60
450	12,80	2500	32,50
900	18,60	5800	50,00

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli

Tel +39-382.815150 Fax +39-0382.814212

Date

05/06/2017

Responsible

Alberto Scardovi