


# WISI MULTISYSTEM QUICK, cascadable 9 inputs

\* Switches can be addressed with 14/18 V, 22 kHz  
but only 4 inputs can be controlled  
EMC acc. to CE, Class A


## DY 94 A



## DY 96 A



## DY 98 A



Type	DY 94 A Multiswitch, cascadable	DY 96 A Multiswitch, cascadable	DY 98 A Multiswitch, cascadable
Trunk	Trunk	Trunk	Trunk
Inputs SAT + TERR	8 + 1	8 + 1	8 + 1
Frequency range TERR	5-862 MHz	5-862 MHz	5-862 MHz
Gain TERR	-	-	-
Output level TERR 3rd ord. EN 50083-3	-	-	-
Thru loss TERR:	5.5 dB	5.5 dB	5.5 dB
Frequency range SAT	950-2400 MHz	950-2400 MHz	950-2400 MHz
Gain SAT	-	-	-
Output level SAT 3rd ord. EN 50083-3	-	-	-
Thru loss SAT	1.3-3.4 dB	1.3-3.4 dB	1.3-3.4 dB
Cascadable with	DY94A-98A/ DY04-08/ DY90	DY94A-98A/ DY04-08/ DY90	DY94A-98A/ DY04-08/ DY90
Subscriber outputs	4	6	8
Frequency range	5-2400 MHz	5-2400 MHz	5-2400 MHz
Side loss TERR/SAT	21/21-16 dB (5 dB slope)	21/21-16 dB (5 dB slope)	21/21-16 dB (5 dB slope)
Isolation Subsc.-Subsc. TERR/SAT	>42/>30 dB	>42/>30 dB	>42/>30 dB
Control signal	DiSEqC 2.0 *	DiSEqC 2.0 *	DiSEqC 2.0 *
Operating voltage	-	-	-
Power / current consumption	-	-	-
LNB supply voltage	-	-	-
Dimensions	210x140x27 mm	210x140x27 mm	210x140x27 mm
Packing unit	1 piece, 5.8 dm <sup>3</sup> , 0.85 kg	1 piece, 5.8 dm <sup>3</sup> , 0.85 kg	1 piece, 5.8 dm <sup>3</sup> , 0.85 kg
Shipping package	5 pieces, 30 dm <sup>3</sup> , 4,5 kg	5 pieces, 30 dm <sup>3</sup> , 4,5 kg	5 pieces, 30 dm <sup>3</sup> , 4,5 kg