

DC Block

DL 20 G



Housing for DL 20 A

Packing unit	1 piece, bag
Shipping package	40 pieces, 30 dm ³ , 3 kg

Filter

DL 40 B



Return path filter

F-type connectors male and female 75 Ω

Blocking frequency range	1-65 MHz
Passing frequency range	80-862 MHz
Attenuation	> 40 dB
Packing unit	5 pieces, bag
Shipping package	100 pieces, 2.9 dm ³ , 3.5 kg

Tap offs 1-way DM 2...B (F-type connector)

DM 21 B



DM 22 B



DM 24 B



DM 25 B



Type	DM 21 B Tap off, 1-way	DM 22 B Tap off, 1-way	DM 24 B Tap off, 1-way	DM 25 B Tap off, 1-way
Thru loss 5-1000 MHz	1.5-2 dB	1 dB	0.8 dB	0.8 dB
Tap loss 5-1000 MHz	8 dB	12 dB	16 dB	20 dB
Directional attenuation 5-40 MHz	30 dB	35 dB	40 dB	45 dB
Directional attenuation 40-1000 MHz	25 dB	26 dB	28 dB	32 dB
Isolation 5-1000 MHz	-	-	-	-
Screening factor	>85 dB, Class A	> 85 dB, Class A	> 85 dB, Class A	> 85 dB, Class A
Dimensions	55x50x28 mm	55x50x28 mm	55x50x28 mm	55x50x28 mm
Packing unit	5 pieces, bag	5 pieces, bag	5 pieces, bag	5 pieces, bag
Shipping package	100 pieces, 18.4 dm ³ , 5.3 kg	100 pieces, 18.4 dm ³ , 5.3 kg	100 pieces, 18.4 dm ³ , 5.3 kg	100 pieces, 18.4 dm ³ , 5.3 kg

